

Product code	Color
11430020	Silver
11430030	Black

General specifications

Product type	: Floodlight
Mounting type	: Wall - surface, Ground - on pole
Description	: Exterior spotlight with 2000 lumen COB LED, without driver, suitable for outdoor applications where a powerful and ecological light is needed. It can be mounted on the wall or on the ground, through the specific stainless steel bracket. Lito 230 is dimmable on the mains (230V). High protection rating IP66.

Indoor/outdoor lights	: Outdoor
Applications	: Courtyards, Facades, Gardens, Squares

Lighting specifications

Lamps description	: LED 2000lm 19W 3000K
Color temperature (K)	: 3000

Physical specifications

Body	: Die-cast aluminium
Finishes	: Polyester painted, with a special antioxidising pretreatment
Reflector	: Mirror-metallized thermoplastic material
Closing Screen	: Grinded, tempered 8 mm, and heat resistant glass
Gaskets	: Silicone
Screws	: Stainless steel

Electrical specifications

Cable gland	: M12,5 in nickel-plated brass
Supply cable	: H05RN-F 3x0,75 mm ² , 2 mt. length
Voltage (V)	: 220/240
Frequency (Hz)	: 50/60


Weight and dimensions

Length (mm)	: 160
Width (mm)	: 28
Height (mm)	: 155
Weight (Kg)	: 1.2


Optical specifications

Light distribution	: Symmetric
Light emission	: Direct
Light beam (°)	: 38°
Horizontal orientation	: 220°
Note	: 20°, 65° (mirror metallized), 70° (white) optics are available on demand


Accessories



28-3138
Professional
optic device
65°




28-3140
Professional
optic device
20°



28-3141
Professional
optic device
70°

84108
Waterproof
connector

Lamps	Categories	Type	Wattage (W)	Nominal lumens on thermal regime	Color Temp. (K)	CRI
	LED	COB LED	19	2000	3000	>80

Pictures and Applications

