

QUALITY MARKS



COLOURS



NORA

Recessed ceiling luminaire constructed of:









- Painted die-cast aluminium ring and heat sink
- Trasparent safety glass
- Lens 24°-38° for cod. 1210 - 1211
- Satin-matt faceted aluminium reflector with high luminous efficiency for cod. 1810 - 1811 - 1812
- Spring fastening system
- Stainless steel screws
- Painting using high resistance to UV and corrosion polyester powders

NOTES

The luminaire is provided with aluminium reflector

Code	Light source	Power	Lum. Flux *	Colour Temperature	Beam angle	Notes
1810.17X	LED COB	18W	2420 lm	3000 K	50°	With IP20 remote driver
1810.19X	LED COB	18W	2520 lm	4000 K	50°	With IP20 remote driver

* Lumen rating is related to the flux emitted by the LED module and not to the flux emitted by the appliance

	<p>Energy class: 1810.19X This product contains an energy efficiency class (C) light source that complies with Regulation (EU) No 2019/2015 1810.17X This product contains an energy efficiency class (D) light source that complies with Regulation (EU) No 2019/2015</p>		<p>Recessed ceiling version</p>		<p>Single power supply cables input</p>		<p>LED: The luminaire needs a remote power supplier (supplied)</p>
	<p>The luminaire needs a remote power supply (supplied IP20)</p>		<p>On request</p>		<p>On request</p>		<p>Only IP20 on request</p>